

SECTION 1: Identification

1.1. Identification

Product form	: Substance
Trade name	: POLY-SOLV® EM-HP
Chemical name	: ETHANOL, 2-METHOXY-
CAS-No.	: 109-86-4
Formula	: C3H8O2
Synonyms	: Ethanol, 2-methoxy- / Ethylene glycol methyl ether / Ethylene glycol monomethyl ether / Glycol monomethyl ether / Poly-Solv EM / Methyl Cellosolve / Methoxyethanol, 2- / Methyl glycol / EGMME / Glycol methyl ether / Methyl cellosolve

1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Solvent Anti-freezing agent
------------------------------	----------------------------------

1.3. Supplier

Monument Chemical
2450 Olin Road
Brandenburg, KY 40108 - USA
T (270)422-6860
sds@monumentchemical.com - www.monumentchemical.com

1.4. Emergency telephone number

Emergency number	: 24 HR CHEMTREC: 1-800-424-9300 (International +1 703-741-5970); 24 HR Emergency Assistance: 1-270-422-6860
------------------	--

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture


GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (dermal) Category 4	H312	Harmful in contact with skin
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Reproductive toxicity Category 1B	H360	May damage fertility or the unborn child
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)	: 
Signal word (GHS US)	: Danger
Hazard statements (GHS US)	: H226 - Flammable liquid and vapor H312+H332 - Harmful in contact with skin or if inhaled H360 - May damage fertility or the unborn child H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary statements (GHS US)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing fume, mist, vapors.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective clothing, protective gloves.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a doctor, a POISON CENTER if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P322 - Specific treatment (see supplemental first aid instruction on this label)
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO₂), dry extinguishing powder, Water spray to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%
ETHANOL, 2-METHOXY- (Main constituent)	(CAS-No.) 109-86-4	99 – 100

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Specific measures (see Consult a doctor/medical service on this label). Wash with plenty of soap and water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard.

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Ventilation, lighting, electrical equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Ignition sources, Incompatible materials. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ETHANOL, 2-METHOXY- (109-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Methoxyethanol (EGME)
ACGIH TWA (ppm)	0.1 ppm
Remark (ACGIH)	Hematologic eff; repro eff
USA - OSHA - Occupational Exposure Limits	
Local name	2-Methoxyethanol; (Methyl cellosolve)
OSHA PEL (TWA) (mg/m ³)	80 mg/m ³
OSHA PEL (TWA) (ppm)	25 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	200 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	0.3 mg/m ³
NIOSH REL (TWA) [ppm]	0.1 ppm
US-NIOSH chemical category	SK: SYS Apr 2011

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask. Wear respiratory protection.

Personal protective equipment symbol(s):

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Color	: Colorless
Odor	: mild
Odor threshold	: No data available
pH	: 5 – 7 (@ 25 Deg. C)
Melting point	: -85 °C
Freezing point	: -86 °C
Boiling point	: 124 °C
Flash point	: 46 °C
Relative evaporation rate (butyl acetate=1)	: 0.62
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 8.63 mm Hg (@ 25 Deg. C)
Relative vapor density at 20 °C	: 2.62
Relative density	: 0.963
Specific gravity / density	: 8 lb/gal
Molecular mass	: 76.1 g/mol
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: -0.85
Auto-ignition temperature	: 285 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks. Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases.

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Harmful if inhaled.

ETHANOL, 2-METHOXY- (109-86-4)	
LD50 oral rat	2370 mg/kg
LD50 dermal rabbit	1280 mg/kg
LC50 Inhalation - Rat [ppm]	1478 ppm (Exposure time: 7 h)
ATE US (oral)	2370 mg/kg body weight
ATE US (dermal)	1280 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 5 – 7 (@ 25 Deg. C)
Serious eye damage/irritation : Not classified
pH: 5 – 7 (@ 25 Deg. C)
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : May damage fertility or the unborn child.
STOT-single exposure : Not classified
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

ETHANOL, 2-METHOXY- (109-86-4)	
LOAEL (oral,rat,90 days)	71 mg/kg body weight Animal: rat, Animal sex: male
LOAEL (dermal,rat/rabbit,90 days)	1000 mg/kg body weight Animal: rat, Animal sex: male
NOAEL (oral,rat,90 days)	< 71 mg/kg body weight Animal: rat, Animal sex: male

Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.
Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

ETHANOL, 2-METHOXY- (109-86-4)	
LC50 fish 1	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 10000 mg/l (24 h, Daphnia magna)
LC50 fish 2	9650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

12.2. Persistence and degradability

ETHANOL, 2-METHOXY- (109-86-4)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

ETHANOL, 2-METHOXY- (109-86-4)	
Partition coefficient n-octanol/water (Log Pow)	-0.85

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHANOL, 2-METHOXY- (109-86-4)

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapors are flammable. Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1188 Ethylene glycol monomethyl ether, 3, III
UN-No.(DOT)	: UN1188
Proper Shipping Name (DOT)	: Ethylene glycol monomethyl ether
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 127
Other information	: No supplementary information available.

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Transport document description (IMDG) : UN 1188 ETHYLENE GLYCOL MONOMETHYL ETHER, 3, III (38°C c.c.)
UN-No. (IMDG) : 1188
Proper Shipping Name (IMDG) : ETHYLENE GLYCOL MONOMETHYL ETHER
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 1188 Ethylene glycol monomethyl ether, 3, III
UN-No. (IATA) : 1188
Proper Shipping Name (IATA) : Ethylene glycol monomethyl ether
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

ETHANOL, 2-METHOXY- (109-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag	S - S - indicates a substance that is identified in a final Significant New Use Rule.
--------------------------	---

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

POLY-SOLV® EM-HP	CAS-No. 109-86-4	100%
------------------	------------------	------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

POLY-SOLV® EM-HP	CAS-No. 109-86-4	100%
------------------	------------------	------

15.2. International regulations

CANADA

ETHANOL, 2-METHOXY- (109-86-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

ETHANOL, 2-METHOXY- (109-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

ETHANOL, 2-METHOXY- (109-86-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

POLY-SOLV® EM-HP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

ETHANOL, 2-METHOXY- (109-86-4)	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Yes
No significant risk level (NSRL)	63 (oral)
Maximum allowable dose level (MADL)	63 µg/day (oral)
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

⚠ WARNING: This product can expose you to POLY-SOLV® EM-HP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/12/2020
Other information : None.

Full text of H-phrases:

H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H332	Harmful if inhaled
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

DISCLAIMER: Monument Chemical believes that the information expressly set forth in this Safety Data Sheet (SDS) is accurate as of the date of publication. MONUMENT CHEMICAL EXPRESSLY DISCLAIMS ALL WARRANTIES OF EVERY KIND AND NATURE, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Monument Chemical assumes no responsibility for any use of or reliance upon the data provided in this SDS. Given the variety of factors that can affect the use of the material, some of which are uniquely within the user's knowledge and control, the user should independently evaluate (i) the completeness and accuracy of the information provided herein and (ii) the material to determine whether it is suitable and safe for the user's intended use.

Monument Chemical provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Monument Chemical makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Monument Chemical.